

Court Marshall

1. Product and Company Information

Product Name: Praters Court Marshall
Supplier: Praters Incorporated
2712 8th Avenue
Chattanooga, TN, 37407
(800) 295-4839
Manufacturer: Basic Coatings
1001 Brown Avenue
Toledo, Ohio 43607
(800) 333-2156
Code: B1126
MSDS#: B1126
In Case of Emergency: (800) 424-9300
Validation Date: 8/13/2012
Print Date: 10/10/2014
Product Type: Liquid

2. Hazards Identification

EMERGENCY OVERVIEW

Physical State: Liquid
Color: Blue (Light)
Odor: Alcohol-Like
Signal Word: WARNING!
Hazardous Statements: COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.
Precautionary Statements: Do not breathe vapor or mist. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep away from heat and flame. Wash thoroughly after handling.
OSHA/HCS Status: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Routes of Entry: Dermal contact. Eye contact. Ingestion.

Court Marshall

2. Hazards Identification

POTENTIAL ACUTE HEALTH EFFECTS

Inhalation:	No known significant effects or critical hazards.
Ingestion:	No known significant effects or critical hazards.
Skin:	Slightly irritating to the skin
Eyes:	Severely irritating to the eyes.

POTENTIAL CHRONIC HEALTH EFFECTS

Chronic Effects:	Contains material that may cause target organ damage, based on animal data.
Carcinogenicity:	No known significant effects or critical hazards.
Mutagenicity:	No known significant effects or critical hazards.
Teratogenicity:	No known significant effects or critical hazards.
Developmental Effects:	No known significant effects or critical hazards.
Fertility Effects:	No known significant effects or critical hazards.
Target Organs:	Contains material which may cause damage to the following organs: blood, kidneys, liver, spleen, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
Medical Conditions: aggravated by over- exposure	Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicology information (Section 11)

3. Composition/Information on Ingredients

NAME	CAS Number	%
Isopropanol	67-63-0	1-5
1-Methoxy-2-propanol	107-98-2	1-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First Aid Measures

Eye Contact:	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. In case of contact with eyes, rinse immediately with plenty of water.
--------------	--

Court Marshall

4. First Aid Measures

Skin Contact:	In case of irritation, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. If skin irritation persists, seek medical attention.
Inhalation:	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion:	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Protection of First-Aiders:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
Notes to Physician:	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-Fighting Measures

Flammability of Product : Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

EXTINGUISHING MEDIA

Suitable: Use dry chemical, CO₂, water spray (fog) or foam.

Not Suitable: Do not use water jet.

Special Exposure Hazards: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous Thermal: Decomposition Products Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special Protective: Equipment for Fire-Fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental Release Measures

Personal Precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Court Marshall

6. Accidental Release Measures

Environmental Precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

METHODS FOR CLEANING UP

Small Spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosionproof equipment. Dispose of via a licensed waste disposal contractor.

Large Spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and Storage

Handling: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Court Marshall

8. Exposure Controls/Personal Protection

INGREDIENT	EXPOSURE LIMITS
Isopropanol	<p>ACGIH TLV (United States, 2/2010). TWA: 200 ppm 8 hour(s). STEL: 400 ppm 15 minute(s).</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hour(s). TWA: 980 mg/m³ 8 hour(s). STEL: 500 ppm 15 minute(s). STEL: 1225 mg/m³ 15 minute(s).</p> <p>NIOSH REL (United States, 6/2009). TWA: 400 ppm 10 hour(s). TWA: 980 mg/m³ 10 hour(s). STEL: 500 ppm 15 minute(s). STEL: 1225 mg/m³ 15 minute(s).</p> <p>OSHA PEL (United States, 6/2010). TWA: 400 ppm 8 hour(s). TWA: 980 mg/m³ 8 hour(s).</p>
1-Methoxy-2-propanol	<p>ACGIH TLV (United States, 2/2010). TWA: 100 ppm 8 hour(s). TWA: 369 mg/m³ 8 hour(s). STEL: 150 ppm 15 minute(s). STEL: 553 mg/m³ 15 minute(s).</p> <p>OSHA PEL 1989 (United States, 3/1989). TWA: 100 ppm 8 hour(s). TWA: 360 mg/m³ 8 hour(s). STEL: 150 ppm 15 minute(s). STEL: 540 mg/m³ 15 minute(s).</p> <p>NIOSH REL (United States, 6/2009). TWA: 100 ppm 10 hour(s). TWA: 360 mg/m³ 10 hour(s). STEL: 150 ppm 15 minute(s). STEL: 540 mg/m³ 15 minute(s).</p>

Recommended Monitoring Procedures: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering Measures: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene Measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Court Marshall

8. Exposure Controls/Personal Protection

PERSONAL PROTECTION

- Respiratory:** Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands:** Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. <1 hours (breakthrough time): disposable vinyl
- Eyes:** Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: safety glasses.
- Skin:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental Exposure: Contols** Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Personal Protective:
Equipment
(Pictograms)



9. Physical and Chemical Properties

- Physical State:** Liquid
- Flash Point:** Closed cup: 65°C (149°F) [Product does not sustain combustion.]
- Color:** Blue (Light)
- Order:** Alcohol-Like
- PH:** 8.3 to 9.3
- Relative Density:** 0.99388
- Dispersibility Properties:** Easily dispersible in the following materials: cold water and hot water.
- Solubility:** Easily soluble in the following materials: cold water and hot water.

10. Stability and Reactivity

- Chemical Stability:** This Product is Stable
- Conditions to Avoid:** Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

Court Marshall

10. Stability and Reactivity

Incompatible Materials: Reactive or incompatible with the following materials:
oxidizing materials

Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of Hazardous Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological Information

ACUTE TOXICITY

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	DOSE	EXPOSURE
Isopropanol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
1-Methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-

Conclusion/Summary: Not Available

CHRONIC TOXICITY

Conclusion/Summary: Not Available

IRRITATION/CORROSION

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	SCORE	EXPOSURE	OBSERVATION
Isopropanol	Eyes-Moderate Irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes-Moderate Irritant	Rabbit	-	10 milligrams	-
	Eyes-Mild Irritant	Rabbit	-	100 milligrams	-
1-Methoxy-2-propanol	Skin-Mild Irritant	Rabbit	-	500 milligrams	-
	Eyes-Mild Irritant	Rabbit	-	24 hours 100 milligrams	-
	Skin-Mild Irritant	Rabbit	-	500 milligrams	-

Conclusion/Summary: Not Available

SENSITIZER

Conclusion/Summary: Not Available

CARCINOGENICITY

Conclusion/Summary: Not Available

CLASSIFICATION

PRODUCT/INGREDIENT NAME	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Isopropanol	A-4	3	-	-	-	-

Court Marshall

11. Toxicological Information

MUTAGENICITY

Conclusion/Summary: Not Available

TERATOGENICITY

Conclusion/Summary: Not Available

REPRODUCTIVE TOXICITY

Conclusion/Summary: Not Available

12. Ecological Information

ECOTOXICITY

AQUATIC ECOTOXICITY

PRODUCT/INGREDIENT NAME	RESULT	SPECIES	EXPOSURE
Isopropanol	Acute LC50 1400000 ug/L Marine Water	Crustaceans-Crangon Crangon	48 hours
	Acute LC50 1400000 ug/L	Fish-Gambusia Affinis-20 to 30mm	96 hours

Conclusion/Summary: Not Available

PERSISTENCE/DEGRADABILITY

Conclusion/Summary: Not Available

12. Ecological Information

Waste Disposal:

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations. Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Court Marshall

14. Transport Information

REGULATORY INFORMATION	UN NUMBER	PROPER SHIPPING NAME	CLASSES	PG	LABEL	ADDITIONAL INFORMATION
DOT CLASSIFICATION	Not regulated	-	-	-		-
TDG CLASSIFICATION	Not regulated	-	-	-		-
MEXICO CLASSIFICATION	Not regulated	-	-	-		-
ADR/RID CLASS	Not available	Not available	Not available	-		-
IMDG CLASS	Not available	Not available	Not available	-		-
IATA-DGR CLASS	Not available	Not available	Not available	-		-

15. Regulatory Information

HCS Classification: Combustible liquid
Irritating material
Target organ effects

U.S. Federal Regulations: **TSCA 5(a)2 proposed significant new use rules:** 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one
TSCA 8(a) PAIR: Amides, coco, N-[3-(dimethylamino)propyl], alkylation products with sodium 3-chloro-2-hydroxypropanesulfonate; Silicone L-45
TSCA 8(a) IUR Exempt/Partial exemption: Not determined
United States inventory (TSCA 8b): All components are listed or exempted.
TSCA 8(d) H and S data reporting: Silicone L-45

SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: 1-Methoxy-2-propanol; Isopropanol
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 1-Methoxy-2-propanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard; Isopropanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

Clean Water Act (CWA) 307: disodium [29H,31H-phthalocyaninedisulphonato(4-)-N29,N30,N31,N32]cuprate(2-)

Court Marshall

15. Regulatory Information

Clean Air Act Section:
112(b) Hazardous Air
Pollutants (HAPs) Not Listed

Clean Air Act Section 602:
Class I Substances Not Listed

Clean Air Act Section 602:
Class II Substances Not Listed

DEA List I Chemicals:
(Precursor Chemical) Not Listed

DEA List II Chemicals:
(Precursor Chemical) Not Listed

SARA 313

	PRODUCT NAME	CAS Number	CONCENTRATION
Form-R Reporting Requirements	Isopropanol	67-63-0	1-5
Supplier Notification	Isopropanol	67-63-0	1-5

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

STATE REGULATIONS

Massachusetts: The following components are listed: ISOPROPYL ALCOHOL; PROPYLENE GLYCOL METHYL ETHER

New York: None of the components are listed.

New Jersey: The following components are listed: ISOPROPYL ALCOHOL; 2-PROPANOL; PROPYLENE GLYCOL MONOMETHYL ETHER; 1-METHOXY-2-PROPANOL

Pennsylvania: The following components are listed: Isopropyl blend; 2-PROPANOL, 1-METHOXYState

Canada Inventory: All components are listed or exempted.

INTERNATIONAL REGULATIONS

International Lists:
Australia inventory (AICS): All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
Japan inventory: Not determined.
Korea inventory: All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.

**Chemical Weapons
Convention List Schedule I:
Chemicals** Not Listed

Court Marshall

15. Regulatory Information

INTERNATIONAL REGULATIONS

Chemical Weapons Convention List Schedule I: Chemicals Not Listed

Chemical Weapons Convention List Schedule II: Chemicals Not Listed

Chemical Weapons Convention List Schedule III: Chemicals Not Listed

16. Other Information

Label Requirements: COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE IRRITATION. MAY CAUSE SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (USA)

HEALTH	*	2
FLAMMABILITY		2
PHYSICAL HAZARDS		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (USA)




Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

16. Other Information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of Printing: 10/10/2014
Date of Issue: 10/10/2014
Date of Previous Issue: 12/15/2011
Version: 0.02
Prepared by: Not Available

 Indicates information that has changed from previously issued version.

NOTICE TO READER

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.